

**PERFORMANCE DECLARATION**

**No. 1/2023 of 19.05.2023**



1.	<p>Product type unique identification code: <b>Mass no. 1 (Red), mass no.2 (Brown). Clinker cladding tile</b></p> <p><b>Colours:</b> Ruby red (01), Brown glazed (02), Natural brown (03), Wild wine (04), The secret garden (05), Note of cinnamon (06), Crimson island (07), Polar night (08), Sunny shore (09), Misty morning (12), Golden autumn (13), Tobacco leaf (14), Mahogany dream (15), The cherry orchard (16), Onyx black (17), Volcanic black (18), Ruby flame (19), Tibetan flame (20), Green valley (24), Green hills (25), Black pearl (32), Black diamond (33), Main street (34), Crimson tide (35), Black river (36), Black jack (37), Marrakesh dust (HF01), Bengali sunrise (HF02), Brick tower (HF03), Alhambra sun (HF04), Brick street (HF05), Bengali night (HF06), Old house (HF07), Deep purple (HF08), Tower bridge (HF09), Purple rain (HF10), Manor house (HF11), Red rock (HF12), Bastille wall (HF16), Red house (HF17), Dragon hill (HF18), Dark fortress (HF19), Monastic cellar (HF20), Aria rustica (HF21), Frozen island (HF22), African soul (HF23), Smooth jazz (HF24), Brazilian coffee (HF25), Chocolate tree (HF26), Blues shadow (HF27), Industrial revolution (HF28), Silesian story (HF29), Heart brick (HF30), Irish pub (HF31), Street life (HF32), Red hot (HF33), Small town (HF34), Winter palace (HF35), Royal stronghold (HF36), Wall street (HF37), Never land (HF38), Red square (HF39), Clay land (HF40), Gothic smile (HF41), Templarian treasure (HF42), Old factory (HF50), Old fort (HF51), Vintage town (HF52), Old cathedral (HF55), Old residence (HF57), Magic castle (HF75), Loft city (HF76), Dolomite peak (HF77), Stardust (HF78), Supernova (HF79), Antic city (HF80), Castle forge (LF01), Valyria stone (LF02), Iron clay (LF03), Brick capital (LF04), Black heart (LF05), Argon wall (LF06), Old cathedral (LF07), Coral star (LF08), Asteroid house (LF09), Maghreb fire (LF10), Tibetan flame (LF11), Old amber (LF12), Brick republic (LF13), Castle rock (LF14), Another brick (LF15), Red zeppelin (LF16), King crimson (LF17), Obsidian shadow (LF18).</p> <p style="text-align: right;"><b>Applicable to all formats on our offer.</b></p>															
2.	<p>Intended use(s):</p> <p style="text-align: center;"><b>For wall tiling (as finishing) in interiors and/or exteriors of building structures</b></p>															
3.	<p>Manufacturer:</p> <p style="text-align: center;"><b>King Klinker S.A. 26 – 400 Przysucha Skrzyńsko ul. Przemysłowa 56</b></p>															
4.	<p>Authorised representative: <b>Not applicable</b></p>															
5.	<p>Assessment and Verification of Constancy of Performance (AVCP) system(s) : <b>System 4</b></p>															
6a.	<p>Harmonised standard:</p> <p style="text-align: center;"><b>EN 14411:2012 „Ceramic tiles – Definition, classification, characteristics, assessment and verification of constancy of performance and marking” Annex C, Natural</b></p>															
6b.	<p>Technical assessment body: <b>Not applicable</b></p> <p>Notified body (-ies): <b>Not applicable</b></p>															
7.	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="text-align: center;">Declared performance</th> </tr> <tr> <th style="width: 33%;">General characteristics</th> <th style="width: 33%;">Performance properties</th> <th style="width: 34%;">Harmonized technical specification</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Reaction to fire</td> <td style="text-align: center;">class A1</td> <td rowspan="3" style="text-align: center; vertical-align: middle;"><b>EN 14411:2012</b></td> </tr> <tr> <td style="text-align: center;">Water absorption</td> <td style="text-align: center;">~ 3%</td> </tr> <tr> <td style="text-align: center;">Thermal shock resistance</td> <td style="text-align: center;">Yes</td> </tr> </tbody> </table>			Declared performance			General characteristics	Performance properties	Harmonized technical specification	Reaction to fire	class A1	<b>EN 14411:2012</b>	Water absorption	~ 3%	Thermal shock resistance	Yes
Declared performance																
General characteristics	Performance properties	Harmonized technical specification														
Reaction to fire	class A1	<b>EN 14411:2012</b>														
Water absorption	~ 3%															
Thermal shock resistance	Yes															

7.	<b>External use durability</b>	Yes	<b>EN 14411:2012</b>
	<b>External use durability: resistance to frosting - defrosting</b>	Yes	
	<b>Dimension</b> - Length and width  - Thickness - Squareness - Surface flatness - Curvature of sides	$\pm 2.0\%$ to maximum $\pm 4\text{mm}$  $\pm 10\%$ $\pm 1.0\%$ $\pm 1.5\%$ $\pm 1.0\%$	
	<b>Surface quality</b>	Minimum 95% tiles should not have visible defects causing deterioration of the appearance of considerable surface of tiles.	
	<b>Bonding strength / adhesion</b>  - cement adhesives - dispersion adhesives - reactive resin adhesive - masonry mortar	NPD NPD NPD NPD	

8. Relevant technical documentation or special technical documentation: **Not applicable**

Performance of the above specified product is in conformity with a set of performances declared. This performance declaration is issued in accordance with the Regulation (EU) no. 305/2011 at the exclusive liability of the above mentioned manufacturer.

Signed on behalf of the manufacturer by :  
**Sylwester Czubak**  
Head of Quality Control Department  
Działu Kontroli Jakości  
*mgr inż. Sylwester Czubak*  
/-/ illegible signature  
(signature)

Skrzyńsko 19.05.2023  
.....  
Place and date of issue